

# **Fusion**

# Perforated or Non-Perforated Ceiling & Wall Panels

Fusion acoustic ceiling and wall panels feature wood-veneer face, either in flat panels or with a variety of perforation options. Standard perforations are available in 4mm, 6mm, and 8mm diameter holes spaced 16mm or 32mm on center in both square and diamond patterns. Custom diameter, spacing, and patterns are available, as well as slotted designs. For projects requiring sound absorption, acoustical backer may be installed above Fusion ceiling or behind Fusion wall panels.

### **FEATURES**

#### **APPEARANCE & COLOR**

Available in wood veneer in the species shown below\*
Standard perforations in 4mm, 6mm, and 8mm diameter
Slotted and custom perforations available
Perforation spacing: 16mm and 32mm O.C., typical square
or diamond pattern, or slotted patterns
FSC available
May contribute LEED® projects

FINISHES: Clear lacquer top coat or stained to match Touch-up finish available for field application

CORE / FIRE RATING

Available core materials are: Class A Fire Rated Particle Board Class A Fire Rated MDF

## **ACOUSTICAL ABSORPTION**

Acoustically absorptive when perforated - NRC varies based on the hole pattern

Soundtex applied to back of perforated panels for acoustical absorption

Optional features for sound control: Acoustical backer available in 1" and 2"

#### SIZES

3/4" thickness 2' x 2', 2' x 4', 2' x 6', 2' x 8' (nominal) Available in custom sizes up to 4' x 8'



# **MOUNTING OPTIONS**

Ceilings: Lay-in or tegular lay-in; torsion spring Walls: Z-clip / Z-bar

#### **MODULARS**







# **WOOD SPECIES**



<sup>\*</sup>Natural wood products vary in color and grain. Due to differences in printing, actual color may differ from images above.







